
Unison Dimming Series



GENERAL INFORMATION

The Unison DRd Semi-Recessed Installation Kit allows Unison dimming enclosures to be mounted partially recessed for minimal protrusion from the wall. The kit includes a trim cover for a finished look, while maintaining proper cooling.

APPLICATIONS

- Schools
- Restaurants
- Offices
- Town halls
- Houses of Worship

GENERAL

- For use with DRd-6 and DRd-12 Unison enclosures
- Mounting area for BatteryPack option kit
- Meets the following guidelines for maximum protrusion when installed with 6" wall construction:
 - ADAAG 307.2
 - DOJ Standards for accessible design 4.4.1
 - International Building Code IBC1003.3.3
- * Note: actual protrusion will vary based on thickness of finishing materials used during construction and finishing of the wall.


ORDERING INFORMATION

Unison Semi-Recessed Installation Kit

MODEL	DESCRIPTION
DRd6-RIK	Semi-Recessed Installation Kit for DRd6 enclosure
DRd12-RIK	Semi-Recessed Installation Kit for DRd12 enclosure

Compatible Unison DRd Dimming Enclosures

MODEL	DESCRIPTION		
DRd6-12-230	6-module rack enclosure (12 circuits)		
DRd12-24-230	12-module rack enclosure (24 circuits)		



Unison Dimming Series

SPECIFIC ATIONS

MECHANICAL

- Welded 18-gauge formed steel enclosure
- Fine textured, scratch-resistant epoxy paint
- Color-matched trim plate
- Mounting hardware included for affixing DRd into Semi-Recessed installation kit.
- 1/4" mounting holes provided on left and right panel edges for securing recess kit to structure
- Integral trim-plate adjustment rails allow for adjustment of trim plate to recess depths from 3.5 to 7"
- Typical protrusion from wall with this kit:
 - 6" in 2x4 construction
 - 4" in 2x6 construction


$\mathsf{P}\,\mathsf{H}\,\mathsf{Y}\,\mathsf{S}\,\mathsf{I}\,\mathsf{C}\,\mathsf{A}\,\mathsf{L}$

Unison DRd Semi-Recessed Installation Kit Dimensions

RACK TYPE	HEIGHT		WIDTH		DEPTH	
	inches	mm	inches	mm	inches	mm
DRd6 Semi- Recessed Kit	32.25	819	20	508	4	102
DRd12 Semi- Recessed Kit	41.5	1,054	20	508	4	102
DRd6 Semi- Recessed Kit with DRd6 installed	32.25	819	20	508	10	250
DRd6 Semi- Recessed Kit with DRd12 installed	41.5	1,054	20	508	10	250

Unison DRd Semi-Recessed Installation Kit Weights

RACK TYPE	WEIGHT		SHIPPING WEIGHT		
	lbs	kgs	lbs	kgs	
DRd6 Semi- Recessed Kit	15	6.8	35	15.9	
DRd12 Semi- Recessed Kit	19	9	42.7	19.4	





Corporate Headquarters • 3031 Pleasant View Rd, PO Box 620979, Middleton WI 53562 0979 USA • Tel +1 608 831 4116 • Fax +1 608 836 1736 London, UK • Unit 26-28, Victoria Industrial Estate, Victoria Road, London W3 6UU, UK • Tel +44 (0)20 8896 1000 • Fax +44 (0)20 8896 2000 Rome, IT • Via Pieve Torina, 48, 00156 Rome, Italy • Tel +39 (06) 32 111 683 • Fax +44 (0) 20 8752 8486 Holzkirchen, DE • Ohmstrasse 3, 83607 Holzkirchen, Germany • Tel +49 (80 24) 47 00-0 • Fax +49 (80 24) 47 00-3 00 Hong Kong • Room 1801, 18/F, Tower 1 Phase 1, Lenterpise Square, 9 Sheung Yuet Road, Kowloon Bay, Kowloon, Hong Kong • Tel +852 2799 1220 • Fax +852 2799 9325 Web • www.etcconnect.com • Copyright©2013 ETC. All Rights Reserved. All product information and specifications subject to change. 7183L1027 Rev. A USA 01/13