



Creating better fog since 1980

M3e

The Maximum output generator
that take your fog to the MAX...

evolution

easy control

energy **e**fficient

exceptional results



... just got better.

Nice work.

PRELIMINARY TECHNICAL DATA

- Single high output
- 100% Duty Cycle
- Variable fog output
- Last operation mode memory
- Recordable failure / anomaly logs
- Firmware upgradable
- Automatic Purging System™ (APS™)
- Maximum Gas pressure input: 4.14 Bar (60 PSI)
- 4 standard USITT DMX512 channels, XLR-5, 1 input, 1 output
- RDM compliant device.
- USB 2.0 Link connector (control)

M3e

Maximum fog output (per minute)	125 m ³ (4,400 ft ³)
Fluid consumption (per hour at 2.76 bar/40 psi)	1.5 L (51 oz)
Gas type	CO ₂ or N ₂
CO ₂ consumption (per hour at 2.76 bar/40 psi)	1,5 kg (3.3 Lb)
Control	4-button LCD user interface, 3 channels DMX XLR-5 connectors, RDM compliant device
Reservoir capacity	2,5 L (0.66 US gallon)
Automatic Purging System (APS)	Standard feature
Fog colour	Pure white
Particle size	0,5 - 0,7 micron
Warm-up time (maximum)	8 minutes
Fluid type (M.S.D.S. available on request)	MDG Neutral Fluid
Operating voltage	100-250 VAC, 50/60 Hz single phase
Power consumption	715 W
Dimension	Length 61 cm (24") Width 18 cm (7") Height 30 cm (12")
Weight	15.62 Kg (35 lb)
Shipping weight (without flight case)	20.42 Kg (45 lb)
Shipping weight (with flight case)	29.12 Kg (64 lb)
Approval	CE, CSA and UL

ACCESSORIES

Portable option

CO₂ adaptor secures gas canister horizontally below machine

**Flight case**

Durable for safe easy transport



FLUID

MDG Neutral Fluid

Safe, non-toxic, with the longest hanging time. Available in 4 L (1 US gallon), 5 L (Europe only), 20 L (5.3 US gallon), 205 L (55 US galon) and 1000 L (264 US gallon) sixes.



MDG

Creating better fog since 1980

10301 av. Pelletier, Montréal, Québec, Canada H1H 3R2
T (514) 272-6040 1-800-663-3020 F (514) 722-3229
info@mdgfog.com www.mdgfog.com